

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

Application Serial No. . . . . Filed Herewith  
Filing Date . . . . . Filed Herewith  
Inventor . . . . . Freddie W. Smith  
Assignee . . . . . Micron Technology, Inc.  
Group Art Unit . . . . . Unknown  
Examiner . . . . . Unknown  
Attorney's Docket No. . . . . MI40-340  
Title: Communication Systems, Communication Apparatuses, Radio Frequency  
Communication Methods, Methods of Communicating Using a Radio Frequency  
Communication System, and Methods of Forming a Radio Frequency  
Communication Device

PRELIMINARY AMENDMENT

To: Box Patent Application  
Assistant Commissioner for Patents  
Washington, D.C. 20231

**EV 026158624**

From: James D. Shaurette (Tel. 509-624-4276; Fax 509-838-3424)  
Wells, St. John, Roberts, Gregory & Matkin P.S.  
601 W. First Avenue, Suite 1300  
Spokane, WA 99201-3828

Sir:

Please enter the following amendments prior to examining the above-identified  
application:

AMENDMENTS

In the Title:

Please replace the title with the following: --Communication Systems,  
Communication Apparatuses, Radio Frequency Communication Methods, Methods of  
Communicating Using a Radio Frequency Communication System, and Methods of  
Forming a Radio Frequency Communication Device--.

20250106 16:52:00

In the Specification

At page 1 before the "Technical Field" section please insert:

**--RELATED PATENT DATA**

This patent resulted from a continuation of and claims priority to U.S. Patent Application Serial No. 09/020,595, filed on February 4, 1998, entitled "Communication Systems, Communication Apparatuses, Radio Frequency Communication Methods, Methods of Communicating Using a Radio Frequency Communication System, and Methods of Forming a Radio Frequency Communication Device", naming Freddie W. Smith as inventor, the disclosure of which is incorporated herein by reference.--.

In the Claims

Please replace the claims with the following clean version of the entire set of pending claims, in accordance with 37 C.F.R. § 1.121(c)(1)(i).

A marked up version showing amendments to any claims being changed is provided in one or more accompanying pages separate from this amendment in accordance with 37 C.F.R. § 1.121(c)(1)(ii).

64. (New) A communication system comprising:  
an interrogator configured to output a radio frequency signal; and  
a communication device configured to communicate with the interrogator and including:

a receive antenna configured to receive the radio frequency signal;  
a backscatter antenna;

a switch configured to selectively short-circuit a plurality of leads of the backscatter antenna providing a first load impedance of the backscatter antenna and a second load impedance of the backscatter antenna less than the first load impedance; and

communication circuitry configured to control the switch to implement backscatter communications using the backscatter antenna during a transmit mode of operation of the communication device, and to provide the switch in an open state during a receive mode of operation of the communication device; and

a transformer coupled with the communication circuitry and the backscatter antenna and configured to transform a load impedance of the backscatter antenna from the first load impedance to the second load impedance during the receive mode of operation of the communication device to provide beam forming of the backscatter antenna and the receive antenna.

65. (New) The system of claim 64 wherein the interrogator and the communication device are configured to communicate using radio frequency identification device communications.

66. (New) The system of claim 64 wherein the transformer comprises at least one transmission line.

67. (New) The system of claim 66 wherein the at least one transmission line has a length equal to approximately one fourth the wavelength of the radio frequency signal.

68. (New) The system of claim 64 wherein the receive antenna and the backscatter antenna are spaced by a distance substantially equal to a wavelength of the radio frequency signal.

69. (New) The system of claim 64 wherein the communication device further comprises a substrate including a plurality of opposing surfaces, and wherein the receive antenna and the backscatter antenna are supported by one of the opposing surfaces and the transformer is supported by the other of the opposing surfaces.

70. (New) A communication apparatus comprising:  
a first antenna;  
a second antenna; and  
communication circuitry coupled with the first antenna and configured to process radio frequency signals received via the first antenna from an interrogator, the communication circuitry being further configured to control the operation of the second antenna between a first load impedance and a second load impedance less than the first load impedance to implement backscatter communications using the second antenna and to provide the second antenna including the second load impedance during receiving of the radio frequency signals using the first antenna.

71. (New) The apparatus of claim 70 further comprising a battery configured to supply electrical energy to the communication circuitry.

72. (New) The apparatus of claim 70 wherein the communication circuitry is configured to process radio frequency signals comprising radio frequency identification device signals.

73. (New) The apparatus of claim 70 further comprising:

a switch; and

a plurality of transmission lines coupled with the switch and individually coupled intermediate the second antenna and the communication circuitry, and wherein the communication circuitry is configured to open the switch to provide the second antenna including the second load impedance during the receiving of the radio frequency signals.

74. (New) The apparatus of claim 73 wherein the transmission lines individually have a length equal to approximately one fourth the wavelength of the radio frequency signals.

75. (New) The apparatus of claim 73 further comprising a substrate including a plurality of opposing surfaces, wherein the first antenna and the second antenna are supported by one of the opposing surfaces and the transmission lines are supported by the other of the opposing surfaces.

76. (New) The apparatus of claim 70 wherein the first antenna and the second antenna are spaced by a distance substantially equal to a wavelength of the radio frequency signals.

77. (New) A communication apparatus comprising:

a receive antenna adapted to receive radio frequency signals from an interrogator;

a dipole antenna including a plurality of halves;

communication circuitry configured to selectively electrically short the halves to communicate backscatter signals to the interrogator and to substantially electrically insulate the halves from one another during the receiving of radio frequency signals via the receive antenna; and

a coupler configured to electrically couple the halves with the communication circuitry and to provide a load impedance of the dipole antenna during the electrical insulation of the halves less than a load impedance of the dipole antenna during the electrical shorting of the halves.

78. (New) The apparatus of claim 77 wherein the communication circuitry is configured to selectively electrically short the halves to communicate the backscatter signals to implement radio frequency identification device communications.

79. (New) The apparatus of claim 77 wherein the coupler comprises at least one transmission line including a length equal to approximately one fourth the wavelength of the radio frequency signals.

80. (New) The apparatus of claim 77 wherein the receive antenna and the dipole antenna are spaced by a distance substantially equal to a wavelength of the radio frequency signals.

81. (New) The apparatus of claim 77 wherein the communication device further comprises a substrate including a plurality of opposing surfaces, wherein the receive antenna and the dipole antenna are supported by one of the opposing surfaces and the coupler is supported by the other of the opposing surfaces.

82. (New) A radio frequency communication method comprising:  
receiving a radio frequency signal using a receive antenna of a communication device;

selectively shorting and electrically insulating a plurality of halves of a dipole antenna to communicate a backscatter signal from the communication device;

electrically insulating the halves of the dipole antenna during the receiving; and  
transforming a high load impedance of the dipole antenna to a low load impedance of the dipole antenna during the receiving.

83. (New) The method of claim 82 wherein the receiving and selectively shorting comprise receiving and selectively shorting using radio frequency identification device communications.

84. (New) The method of claim 82 wherein the transforming comprises transforming using a transformer including a length equal to approximately one fourth the wavelength of the radio frequency signal.

85. (New) The method of claim 82 further comprising providing the receive antenna and the dipole antenna spaced by a distance substantially equal to a wavelength of the radio frequency signal.

86. (New) A method of communicating using a radio frequency communication system, the method comprising:

outputting a wireless interrogation signal using an interrogator;

receiving the wireless interrogation signal using a receive antenna of a remote communication device;

controlling a load impedance of a return link antenna of the remote communication device between a first load impedance and a second load impedance less than the first load impedance to communicate information from the remote communication device to the interrogator responsive to the receiving; and

providing the return link antenna including the second load impedance during the receiving.



87. (New) The method of claim 86 wherein the outputting and the controlling comprise outputting and controlling to implement radio frequency identification device communications.

88. (New) The method of claim 86 wherein the controlling comprises controlling a switch intermediate a plurality of transmission lines which couple the return link antenna and communication circuitry configured to control the switch.

89. (New) A method of forming a radio frequency communication device comprising:

providing a substrate;

coupling communication circuitry configured to process received radio frequency signals with the substrate;

providing a receive antenna and a dipole antenna over the substrate and spaced by a distance substantially equal to a wavelength of the radio frequency signals; and

coupling the dipole antenna and the communication circuitry using a connection including a length equal to approximately one fourth the wavelength of the radio frequency signals; and

coupling the receive antenna and the communication circuitry.

90. (New) The method of claim 89 wherein the coupling communication circuitry comprises coupling radio frequency identification device communication circuitry.

91. (New) The method of claim 89 wherein the coupling communication circuitry comprises coupling communication circuitry configured to control the emission of backscatter signals using the dipole antenna.

92. (New) The method of claim 89 wherein the coupling the dipole antenna and the communication circuitry comprises coupling using the connection comprising a transformer comprising at least one transmission line.

93. (New) The method of claim 89 wherein the providing the substrate comprises providing the substrate including a plurality of opposing surfaces, and wherein the receive antenna and the dipole antenna are supported by one of the opposing surfaces and the connection is supported by the other of the opposing surfaces.

94. (New) The method of claim 89 further comprising:  
supporting a battery using the substrate; and  
electrically coupling the battery with the communication circuitry.

### REMARKS

This application is a continuation application of U.S. Patent Application Serial No. 09/020,595, filed on February 4, 1998. Claims 1-63 have been canceled without prejudice. Claims 64-94 are pending in the application, and Applicant requests examination of such pending claims.


The Examiner is requested to phone the undersigned if the Examiner believes such would facilitate prosecution of the present application. The undersigned is available for telephone consultation at any time during normal business hours (Pacific Time Zone).

Respectfully submitted,

Dated: \_\_\_\_\_

2/12/02

By: \_\_\_\_\_

  
James D. Shaurette  
Reg. No. 39,833